

# FAXCONT FC-K102

Dome / Camera Controller



FC CE

## Overview

The FC-102 keyboard is specially designed for FAXCONT® series Dome/Camera controller. The operator can take direct control of up to 1024 Dome/Cameras or pan/tilt (with FAXCONT® decoder) with the FC-102.

Keys are provided for control of motorized lens functions (IRIS and focus, as well as zoom) and activation of user programmable Presets, Patterns, and auxiliaries for suitably equipped domes and pan/tilts. The control applications, for instance: camera power switch, auxiliary lighting, siren, pan/tilt control, wiper switch and warming-up of outdoor housing. The LCD display window indicates the currently selected camera, as well as the numbers entered from the keypad.

## Main Features

- Manual control of up to 1024 Dome/Cameras and pan/tilt: IRIS, focus, zooms, ratio, up, down, left, right.
- Connects FAXCONT® Outdoor or Indoor decoder between keyboard and any other brand camera's or pan/tilts. The keyboard can also control these devices.
- Auto-pan angle can be setup, auto-pan start and stop for any selected pan/tilt.
- Each speed dome can be preset up to of 128 positions; each position is dwell time 1 ~ 99 sec.
- Each speed dome includes 4 auto-scan groups, each group with 8 preset positions.
- Up to 16 sets of FAXCONT® series keyboard controller can be linked.
- LCD displays the current control status.
- 1024 alarm address, monitor arm/disarm control and alarm manual acknowledgement.

## Specifications

- Communication Protocol: RS485, Twist pair wires
- Baud Rate: 1200 ~ 9600bps
- Control Port: RS485 x 1
- Data Transmission Distance: 1.5Km
- Power: DC 9/12V
- Power Consumption: 10W