

FAXCONT FC-607

Camera Housing



Overview

- Outdoor top open camera housing.
- Top : ABS & PC / Bottom : Aluminum / Sun-Shield : Aluminum
- Appearance Size: 157 (W) x 130 (H) x 460 (L) mm
- Suitable Camera Size: 108 (W) x 75 (H) x 300 (L) mm
- Compliance to IP66 and IK10 vandal proof certification.
- Built-in Fan & Heater (Optional)
- FEVE Coating: Endure harsh environment, prevents acid and base moisture, five years warranty. (Optional)
- IR LAMP. (Optional)
- Wireless. (Optional)
- FC-81 RJ45 Water Proof Connector. (Optional)
- POE Splitter. (Optional)
- POE Power Mixer. (Optional)

Related Products



FC-9014




FC-9015



FC-9017



FC-9003




FC-9010



FC-81



FC-82



FC-83



HB12-8.0



HB24-8.0



Full Range



IR607-3015&4530

Order Information

- FC-607 Housing
- FC-607 Plug and play Housing (With FC-81 IP68 Quick connector)
- FC-607 IR Housing
- FC-607 PoE Housing
- FC-607 Wireless Housing
- FC-607-OR Housings with Oring in front

Application



FC-607 Housing



Plug and play Housing



FC-607 IR Housing
(With sun shield)



PoE Housing
(With sun shield)



Wireless Housing
(With sun shield)



IP66 FC CE



Operation temperature sensor

- Heater : Below 10°C sensor ON (±3°C)
Up to 20°C sensor OFF (±3°C)
When sensor ON, Heater and Fan ON
- Fan : Up to 35°C sensor ON
Below 25°C sensor OFF (±3°C)
When sensor ON, fan ON
- Operation temp : -20°C~50°C
- In 12V DC · Consumption 15W Max.(not include camera)

Temperature control board (Optional)

- All series with surge & over load protector
- HB12-8.0→DC12V driver
Total consumption no more then 60W
- HB24-8.0→Input : AC24V
Output : 1. DC12V(3A)
2. AC24V(Looping)
Total consumption no more then 65W
P3040 PoE splitter →input : PoE in
Output : 1. DC12V
2. DC24V
- Total consumption no more then 30W

IR LAMP.(Optional)

Model	IR607-3015	IR607-4530
IR Wave Length	850nm	850nm
IR Distance	Over 50 Meters	Over 35 Meters
IR H.V. Angle	30°	45°
IR LEDs	8mm LED 28 units	8mm LED 28 units
Expected Lifetime	> 25000hr	> 25000hr
Status	Auto Control(<3 Lux ON)	Auto Control(<3 Lux ON)
Power	DC12V	DC12V