



IP68 FC CE



**Overview**

- Outdoor top open camera housing.
- Top : Aluminum / Bottom : Aluminum / Sun-Shield : Aluminum
- Appearance Size: 157 (W) x 140 (H) x 340 (L) mm
- Suitable Camera Size: 108 (W) x 75 (H) x 180 (L) mm
- Compliance to IP68 and IK10 vandal proof certification.
- Built-in Fan & Heater (Optional)
- FEVE Coating: Endure harsh environment, prevents acid and base moisture, five years warranty. (Optional)
- IR LAMP. (Optional)
- POE Splitter. (Optional)

**Related Products**



FC-9014



FC-9015



FC-9018



FC-9003



FC-9010



Camera Holder



HB12-8.0



HB24-8.0



P3040.1 POE Splitter



HB00-1.0



IR607-3015&4530



PPM-301

**Order Information**

- FC-608 Housing
- FC-608 IR Housing
- FC-608 POE Housing
- FC-608D Housing

**Application**



FC-608 Housing



FC-608 Housing  
with sun shield



FC-608 IR Housing  
with sun shield



FC-608D Housing




FC-608D Housing  
with sun shield



# FAXCONT FC-608

## Camera Housing



 IP68 FC CE

### Operation temperature sensor

- Heater : 10°C ON , 20°C OFF ( $\pm 3^{\circ}\text{C}$ )
- Fan : 35°C ON , 25°C OFF ( $\pm 3^{\circ}\text{C}$ )  
Sync operation according to heater ON/OFF
- Operation temp :  $-20^{\circ}\text{C} \sim 50^{\circ}\text{C}$
- Power consumption : 20W(not include camera)

### Temperature control board (Optional)

- All series with surge & over load protector
- HB12-8.0  $\rightarrow$  DC12V driver  
Total consumption no more then 60W
- HB24-8.0  $\rightarrow$  input : AC24V  
Output : 1.DC12V(3A)  
2.AC24V(Looping)  
Total consumption no more then 65W
- P3040.1 PoE splitter  $\rightarrow$  input : PoE in  
Output : 1.PoE out  
2.DC12V  
Total consumption no more then 30W

### IR LAMP. (Optional)

Model	IR607-3015	IR607-4530
IR Wave Length	850nm	850nm
IR Distance	Over 50 Meters	Over 35 Meters
IR H.V. Angle	30°	45°
IR LEDs	8mm LED 28 units	8mm LED 28 units
Expected Lifetime	>25000hr	>25000hr
Status	Auto Control (< 3 Lux ON)	Auto Control (< 3 Lux ON)
Power	DC12V	DC12V